



**NOTES:**

1. ALL MATERIAL TO MEET FILTREXX® SPECIFICATIONS.
2. GROSOXX™ FILL TO MEET APPLICATION REQUIREMENTS.
3. ALL GROSOXX™ TO BE SEEDED PER LANDSCAPE ARCHITECT'S SPECIFICATIONS.
4. BACKFILL TO BE PLACED PER ENGINEER'S REQUIREMENTS.
5. GEOGRID STRENGTH, LENGTH AND VERTICAL SPACING TO BE DETERMINED BY ENGINEER. GEOGRID – NO STRANDS ARE TO BE CUT DURING PLANTING, ETC. WE RECOMMEND BI-DIRECTIONAL STRENGTH FOR CONSTRUCTION EASE.
6. NATIVE AND DRAINAGE BACKFILL TO BE SEPARATED BY NON-WOVEN FILTER FABRIC.
7. MAXIMUM HEIGHT RECOMMENDED: TEN FEET EXPOSED HEIGHT.
8. FILTREXX® GROSOXX™ DEPENDS ON APPLICATION (SIZE DEPENDENT ON PROJECT)
9. CUT BANK NO STEEPER THAN 2H:1V. FOR STEEPER EMBANKMENTS, REFER TO GREENLOXX SYSTEM.